


Chimney Offset Table



O = Offset; H = Height

Part No.	2 Elbows w/o Pipe		2 Elbows + 6" Section		2 Elbows + 9" Section		2 Elbows + 12" Section		2 Elbows + 18" Section		2 Elbows + 24" Section		2 Elbows + 36" Section		2 Elbows + 48" Section	
	O	H	O	H	O	H	O	H	O	H	O	H	O	H	O	H
5GT/UT - EL 15°	0.93	7.03	2.16	11.62	2.94	14.52	N/A	N/A	5.72	23.21	N/A	N/A	9.92	40.60	N/A	N/A
6GT/UT - EL 15°	1.04	7.88	2.27	12.47	3.05	15.37	3.82	18.26	5.38	24.06	6.92	29.85	10.03	41.25	13.03	53.04
7GT/UT - EL 15°	1.00	7.62	2.23	12.21	3.01	15.11	3.78	18.00	5.34	23.80	6.89	29.59	10.00	41.19	13.10	52.78
8GT/UT - EL 15°	0.97	7.36	2.20	11.95	2.98	14.85	3.75	17.74	5.31	23.54	6.85	29.33	9.96	40.93	13.07	52.52
*5GT/UT - EL 30°	3.64	13.59	6.02	17.70	7.52	20.30	9.02	22.90	12.02	28.10	15.02	33.29	21.02	43.69	27.02	54.08
*6GT/UT - EL 30°	4.08	15.23	6.45	19.34	7.96	21.94	9.45	24.54	12.45	29.74	15.45	34.93	21.45	45.33	27.45	55.72
*7GT/UT - EL 30°	3.95	14.73	6.33	18.84	7.83	21.44	9.33	24.04	12.33	29.24	15.33	34.43	21.33	44.83	27.33	55.22
*8GT/UT - EL 30°	3.81	14.23	6.19	18.34	7.69	20.94	9.19	23.54	12.19	28.74	15.19	33.93	21.19	44.33	27.19	54.72
5GT/UT - EL 30°	3.67	13.75	6.05	17.86	7.55	20.46	N/A	N/A	12.05	28.26	N/A	N/A	21.05	43.84	N/A	N/A
6GT/UT - EL 30°	3.82	14.26	6.20	18.37	7.70	20.97	9.19	23.57	12.20	28.76	15.20	33.96	21.20	44.35	27.20	54.75
7GT/UT - EL 30°	3.96	14.76	6.34	18.87	7.84	21.47	9.33	24.07	12.34	29.26	15.34	34.46	21.34	44.85	27.34	55.25
8GT/UT - EL 30°	4.09	15.26	6.47	19.37	7.97	21.97	9.46	24.57	12.46	29.76	15.47	34.96	21.47	45.35	27.47	55.75
10GT/UT - EL 15°	1.24	9.43	2.47	14.02	3.25	16.92	4.02	19.81	5.58	25.61	7.12	31.40	10.23	43.00	N/A	N/A
12GT/UT - EL 15°	1.00	7.72	2.23	12.31	3.01	15.21	3.78	18.10	5.33	23.90	6.88	29.69	9.99	41.28	N/A	N/A
14GT/UT - EL 15°	1.06	8.25	2.29	12.84	3.07	15.74	3.84	18.63	5.39	24.43	6.95	30.22	10.05	41.82	N/A	N/A
10GT/UT - EL 30°	3.92	15.18	6.30	19.29	7.80	21.89	9.30	24.49	12.30	29.70	15.30	34.88	21.30	45.27	N/A	N/A
12GT/UT-EL30°	3.92	14.63	6.30	18.74	7.80	21.34	9.30	23.93	12.30	29.14	15.30	34.33	21.29	44.72	N/A	N/A
14GT/UT-EL30°	4.19	15.63	6.57	19.74	8.07	22.34	9.56	24.93	12.57	30.14	15.57	35.33	21.56	45.72	N/A	N/A
16GTL-EL30°	6.30	24.70	8.65	28.80	N/A	N/A	11.68	34.02	14.68	39.22	17.68	44.42	23.68	54.81	N/A	N/A
18GTL-EL30°	6.55	25.70	8.90	29.80	N/A	N/A	11.92	35.02	14.92	40.22	17.90	45.42	23.90	55.81	N/A	N/A
20GTL-EL30°	6.80	26.70	9.20	30.80	N/A	N/A	12.20	36.02	15.20	41.22	18.20	46.42	24.20	56.81	N/A	N/A
22GTL-EL30°	7.13	27.70	9.45	31.80	N/A	N/A	12.46	37.02	15.45	42.22	18.45	47.42	24.45	57.81	N/A	N/A
24GTL-EL30°	7.35	28.70	9.75	32.80	N/A	N/A	12.75	38.02	15.75	43.22	18.75	48.42	24.75	58.81	N/A	N/A

Note: All dimensions and indicated lengths assume a 1/4 overlap
 A 30 degree Elbow for 12" & 14" consists of two 15 degree Elbows.
 5 through 10"; 15° elbows are new 2 gore design.
 *are for a pair of 15° elbows.

15° Insulated Elbows can be used for fixed offsets of 15° slope or in pairs for offsets adjustable from 0° to 30° slope. The 30° Insulated Elbow in 5", 6", 7" and 8" sizes can be used for fixed offsets of 30° slope. Greater angles are prohibited by UL® Standard 103 and by the terms of the product listing.

REQUIRED: Locking Bands (2 packaged with each elbow kit) are to be used at each joint. Each offset must be resupported. Elbows rotate 360° to provide the exact orientation required. Insulated Elbows can be used at the same 2" airspace clearance as chimney sections.

